SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Henry[®] 345 Premixed Patch n' Level

Product Identifier Product ID No. Trade Name/Synonyms Material Use Uses Advised Against

: 70012012 : Henry 345 : Floor Patch and Smoothing Compound. : No information available. :

Manufacturer's name and address:



The W.W. Henry Company 400 Ardex Park Drive Aliquippa, PA 15001 USA

Information Telephone No. Website Address 24 Hr Emergency Telephone #

: (724) 203-8000 : http://www.wwhenry.com

: CHEM-TEL: 1-800255-3924 OR 1-813-248-0585 (call collect)

SECTION 2 – HAZARDS IDENTIFICATION

.

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

Skin corrosion/irritation, Category 2 (Irritant) Serious eye damage/eye irritation, Category 2B (Irritant). Carcinogenicity, Category 2

GHS Pictograms

Signal Word	Warning.
Hazard Statements	Suspected of causing cancer. Causes skin irritation. Causes eye irritation.
Precautionary Statements	
	Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection. Wash hands and exposed skin thoroughly after handling. Do not subject to grinding. Store locked up. Dispose of contents / container in accordance with federal, state, and local laws. Do not allow product to enter drains.
Hazards Not Otherwise Classified	None
% With Unknown Acute Toxicity :	Up to 80% by weight of this product is comprised of ingredients with unknown acute toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Crystalline silica	14808-60-7	60. – 100.
2-Butoxyethanol	111-76-2	0.10 – 1.00

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

	SECTION 4 – FIRST AID MEASURES			
General	: Call a Poison Center or doctor if you feel unwell.			
Inhalation	: If inhaled, move victim to fresh air and keep at rest in a position comfortable for breathing. If breathing difficulties persist, seek immediate medical attention/advice.			
Skin contact	: Remove/Take off immediately all contaminated clothing. Flush affected skin with gently flowing lukewarm water for at least 20 minutes. If rash or irritation persists, seek medical attention/advice.			
Eye contact	: Immediately flush eyes thoroughly with running water for at least 20 to 30 minutes. Seek immediate medical attention/advice.			
Ingestion	: Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Seek immediate medical attention/advice.			
Notes for Physician	: Treat symptomatically.			
Signs and symptoms of short-ter	rm (acute) exposure			
Inhalation	: May cause minor, temporary irritation to respiratory tract. Symptoms may include coughing and shortness of breath.			
Skin	: May cause skin irritation. Symptoms may include redness and itching.			
Eyes	: Causes irritation to eyes. Symptoms may include redness, itching, blurred vision or pain.			
Ingestion	: Symptoms such as gastric pain, nausea, vomiting, and diarrhea may occur.			
Effects of long-term (chronic) ex	posure			
	: Prolonged inhalation may cause adverse lung effects with symptoms including coughing and shortness of breath.			
Indication of need for immediate m	edical attention or special treatment			
	: Difficulty breathing persists after removing the person to fresh air.			
	Any exposure to the eye which causes irritation.			
	Ingestion.			
SEC	CTION 5 – FIRE FIGHTING MEASURES			
Suitable extinguishing media	: Carbon dioxide, dry chemical powder, appropriate foam or water fog.			
Unsuitable extinguishing media	: water jet			
Hazardous combustion products	: Carbon monoxide, carbon dioxide, and other toxic vapors and gases which are common to thermal degradation of organic compounds.			
Special fire-fighting procedures/eq	uipment			
	: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.			
Environmental precautions	: Do not allow material to enter drains or contaminate ground water system.			
Fire hazards/conditions of flammal	bility			
	: Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.			
Flammability classification (OSHA 29 CFR 1910.1200, WHMIS2015)				
-	: Not flammable			

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions	: Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.
Protective equipment	 Refer to Section 8 on this Safety Data Sheet, EXPOSURE CONTROLS / PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.
Emergency Procedures	: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).
	US CERCLA Reportable quantity (RQ): None reported.
Methods and materials for contain	ment and cleaning up
	: Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm soapy water. Notify the appropriate authorities as required.
Prohibited materials	: Avoid strong oxidizing agents
Environmental precautions	: Do not allow product to enter drains or waterways. Do not allow material to contaminate ground water system.
Reference to other sections	: See Section 14 for disposal information.

SECTION 7 – HANDLING AND STORAGE

Safe handling procedures :	Observe good hygiene standards. Use only with adequate ventilation. Do not eat, drink or smoke in the work area. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Avoid repeated or prolonged skin contact. Avoid breathing vapors or mists of this product. Sanding and grinding dusts may be harmful if inhaled. When removing this product from existing flooring (i.e. during a renovation), wear safety goggles and respiratory protection from dust due to blasting, chipping, or mechanically pulverizing. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.
Storage requirements :	Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Avoid storing in direct sunlight. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.
Incompatible materials	See Section 10.
Special packaging materials	Always keep in containers made of the same materials as the supply container.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

	exposure limits have bee s for the components in		the produc	ct itself. Below are e	xposure
Ingredients	CAS #	ACGIH T	LV	OSHA PI	EL
		TWA	STEL	PEL	STEL
Crystalline silica	14808-60-7	0.025 mg/m ³ (respirable fraction)	N/A∨	0.1 mg/m ³ (respirable) (Final rule limit)	N/Av
2-Butoxyethanol	111-76-2	20 ppm	N/Av	50 ppm (skin)	N/Av
rec	: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product.				nd prevent
Personal Protection Equipment					
	ety glasses must be wo orne dust is generated,			t. During operatior	is where

Skin protection	: Wear chemical resistant protective clothing and impervious gloves. Glove materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended. Consult with the glove manufacturer regarding breakthrough time for the components listed in Section 3.
Body protection	: Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.
Respiratory protection	 If work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear an appropriate organic vapor respirator or particulate respirator (dust mask) rated N-95 or higher, appropriate for the conditions.
Site safety equipment	: An eyewash station and safety shower should be made available in the immediate working area.
General hygiene considerations	: Avoid contact with eyes, skin and clothing. Avoid breathing vapors/dust. Do not eat, drink or smoke when using this product. Clean all equipment and clothing at end of each work shift.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state		Paste	Appearance		off-white paste
•			••		•
Odor	:	Mild	Odor threshold	:	N/Av
рН	:	7.2 – 7.4	Specific gravity	:	1.53 – 1.64
Boiling point	:	> 212°F (> 100°C)	Coefficient of water/oil distribution	:	N/Av
Melting/Freezing point	:	N/Av	Solubility in water	:	Slightly soluble
Vapor pressure (mm Hg @ 20°C / 68°F)	:	N/Av	Evaporation rate (<i>n</i> -Butyl acetate = 1)	:	N/Av
Vapor density (Air = 1)	:	N/Av	Volatiles (% by weight)	:	14 – 16
Volatile Organic Compounds (VOCs)	:	12.5 g/L SCAQMD	Rule 1168		
Particle size	:	N/Av	Flammability classification	:	Not flammable
Flash point	:	>212°F (100°C)	Lower flammable limit (% by vol)	:	Not available
Flash point method	:	Setaflash closed	Upper flammable limit (% by vol)	:	Not available
Auto-ignition temperature	:	N/Av	Decomposition temperature	:	Not available
Viscosity	:	Not available	Oxidizing properties	:	Not available
Explosion data: Sensitivity to mec	ha	nical impact / sta	tic discharge		

: Not expected to be sensitive to mechanical impact or static discharge.

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

Reactivity	:	Does not react.
Stability :	:	Stable under the recommended storage and handling conditions prescribed.
Hazardous reactions	:	Hazardous polymerization does not occur.
Conditions to avoid :	:	High temperatures.
Materials to avoid and incompatability	1	
:	:	Oxidizing agents.
Hazardous decomposition products	5	
		Next the second state to second state and second state to Ocean second state to Ocean state to Ocean second state to Ocean state sta

: None known, refer to hazardous combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of exposure	:	Inhalation: YES	Skin Absorption:	NO	Skin and Eyes:	Yes	Ingestion:	YES
Symptoms of exposure	:	See Section 4.						
Calculated Acute Toxicity Estimates	for	the Product						
Inhalation	:	> 30 mg/L						
Oral	:	> 3000 mg/kg						
Dermal	:	> 3000 mg/kg						

Toxicological data

: See below for individual ingredient acute toxicity data.

	LC50 (4 hr)	LD50				
Ingredients	Inhalation, rat	Oral, rat	Dermal, rabbit			
2-Butoxyethanol	450 ppm	250 mg/kg	220 mg/kg			
Crystalline silica, quartz	N/Av	N/Av	N/Av			

Skin corrosion or irritation	: May cause irritation to skin.
Serious eye damage / eye irritation	: May cause irritation to eyes.
Respiratory or skin sensitization	: None known.
Germ cell mutagenicity	: None known.
Carcinogenic status	: This product contains Crystalline silica - Quartz. Crystalline silica - Quartz is classified as carcinogenic by inhalation by IARC (Group 1), ACGIH (Group A2), NTP (Group 1) and OSHA (OSHA Select carcinogen). During normal usage of the product as recommended, airborne dusts will not be present. Do not sand/grind/ chip off excess material, following initial application, unless wearing proper respiratory and eye protection. (See Section 8.)
	This product contains 2-Butoxyethanol. 2-Butoxyethanol is not listed as a carcinogen by NTP or OSHA, classified as Category 3 (not classifiable as to carcinogenicity) by IARC, classified by EPA as "Not likely to be carcinogenic to humans at environmental concentrations at or below the RfC [RfC = 1.6 mg/m ³]", and classified by ACGIH as A3 – Animal Carcinogen (with unknown relevance to humans).
Reproductive toxicity	: None known.
Specific Target Organ Toxicity, Single	e Exposure
	: Not considered to be a hazard during normal usage of the product as recommended.
Specific Target Organ Toxicity, Repe	ated Exposure
	: None known.
Aspiration hazard	: None known.
Additional information	: N/Av

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects	:	The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
Ecotoxicity	:	No data available.
Biodegradability	:	No data available.
Bioaccumulative potential	:	No data available.
Mobility in soil	:	No data available.
PBT and vPvB assessment	:	No data available.
Other adverse effects	:	No data available.

SECTION 13 – DISPOSAL CONSIDERATION

•	 Handle waste according to recommendations in Section 7. You must test your waste using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
Packaging	: Handle contaminated packaging in the same manner as the product.
RCRA	: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory UN Information Number		Shipping Name	Class	Packing Group	Label	
TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None	
TDG Additional Information	None					
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None	
49 CFR/DOT Additional	None				1	

ΙΑΤΑ

: Not regulated for Air Transport

IMDG

: Not regulated for Ocean Transport

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

U.S. State Right To Know Laws

California Proposition 65: Warning! This product contains a chemical known to the State of California to cause cancer.

Other State Right to Know Laws:

Ingredient on State RTK Law?	CAS #	CA	MA	MN	NJ	NY	PA	RI
Crystalline silica, quartz	14808-60-7	No	YES	YES	YES	No	YES	YES
2-Butoxyethanol	111-76-2	YES	YES	YES	YES	No	YES	YES

SECTION 16 – OTHER INFORMATION

HMIS Rating

: <u>* - Chronic Hazard</u> 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe Health: 1 Flammability 1 Reactivity 0 PPE: Gloves, safety glasses Legend

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

CFR: Code of Federal Regulations

DOT: Department of Transportation

DSL: Domestic Substances List

EPA: Environmental Protection Agency

GHS: Globally Harmonized System

HPR: Hazardous Products Regulations

IARC: International Agency for Research on Cancer

Inh: Inhalation

N/Av: Not Available

N/Ap: Not Applicable

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values

TSCA: Toxic Substance Control Act

TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. The W.W. Henry Company will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By:

The W.W. Henry Company 400 Ardex Park Drive Aliquippa, PA, U.S.A. 15001

(724) 203-8000 Visit our Website: http://www.wwhenry.com

Revision date:

: 23-Apr-2015

End of Document