

SAFETY DATA SHEET



Section I - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Latexite[®] Trowel Patch (1gallon, 2gallon)

Manufacturer Name: Dalton Enterprises, Inc.

Item #: 1 gal: 32016; 2 gal: 32051

UPC #: 1 gal: 090932320161; 2 gal: 090932320511 Address: 131 Willow Street Cheshire, CT 06410

Telephone Number: (203) 272-3221

24 Hour Emergency Number: (203) 272-3221

U.S. And Canada: (203) 272-3221

Trade Names and Synonyms: Asphalt Patch Materials

Recommended Use and Restrictions: Filler for asphalt pavement

Section II - HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 2
Serious Eye Damage, Eye Irritation	Category 2
Carcinogenicity	1A

Label Elements

Signal Word: Warning **Hazard Statements:** Harmful if swallowed May cause skin irritation May cause cancer





Precautionary Statements – Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Eyes: Contact may cause irritation.

Skin: Prolonged or repeated contact may cause irritation. **Ingestion:** May cause nausea, vomiting and diarrhea.

Inhalation: May cause irritation

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

No information available

Interactions with Other Chemicals

No information available.

Section III - COMPOSITION

CAS#	Component	% Composition
8052-42-4	Petroleum Asphalt	40-55
1332-58-7	Clay/Arcilla	15-20
14808-60-7	Crystalline Silica	10-25
7732-18-5	Water	25-35

Section IV - FIRST-AID MEASURES

Emergency and First Aid Procedures

General Advice: Present this safety data sheet to the physician in attendance. **Eye Contact:** Flush thoroughly with water. If irritation persists, see a physician.

Skin Contact: Clean exposed area thoroughly with soap and water. If irritation persists see a physician.

Ingestion: If swallowed do NOT induce vomiting. Seek medical attention if symptoms develop.

Inhalation: Move to fresh air if symptoms develop. If irritation persists see a physician.

Most Important Symptoms: Possibility of minor eye and skin irritation.

Indication of Immediate Medical Attention and Special Treatment Needed: Treat Symptomatically

Section V - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: CO2, dry chemical, foam, sand.

Unsuitable Extinguishing Media: N/A

Specific Hazards arising From the Chemical: Combustion may yield fumes, smoke, carbon monoxide and

carbon dioxide.

Special Protective Equipment and Precautions for Firefighters: Wear full protective clothing, including self-contained breathing apparatus (Positive Pressure/Pressure Demand), helmet, and face mask.

Section VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Avoid skin and eye contact, use proper protective equipment recommended in section 8.

Methods and Materials for Containment and Cleanup: Contain spill and dike with inert material (sand, sawdust, dirt, etc.). Place in closed container for proper disposal. Avoid runoff to waterways and sewers. Dispose of in accordance with local regulations.

Section VII - HANDLING AND STORAGE

Precautions for Safe Handling: Store in a dry area, avoid eye contact and wash thoroughly after handling **Conditions for Safe Storage, Including Incompatibilities:** Keep container closed and upright to prevent leakage. Store in a cool, dry, ventilated area. Avoid freezing. Keep container upright to prevent leakage.

Section VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TWA (mg/m ³) OSHA PEL (TWA) (mg/m ³)	
Petroleum Asphalt	0.5 mg/m^3	-
Crystalline Silica	0.025 mg/m^3	(30)/(%SiO2 + 2) mg/m3 TWA, total dust
		(250)/(%SiO2 + 5) mppcf TWA, respirable fraction
		(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction

Engineering Controls: Ensure adequate ventilation

Individual Protection Measures

Eyes/Face: Safety goggles

Skin: Gloves

Respiratory: None required if good ventilation is maintained. This product is an emulsified, encapsulated mixture which greatly reduces the likelihood of exposure to hazardous particles. **Hygienic controls:** Wash thoroughly with soap and water before eating or drinking. Wash

contaminated clothing.

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dark brown to black
Physical State: liquid/paste

Odor: Asphaltic odor

Odor Threshold: N/A

Upper Explosive Limit: N/A

Lower Explosive Limit: N/A

Vapor Pressure: 17mm Hg

Vapor Density: Heavier than air

PH: 7.5 – 9.5 **Specific Gravity:** 1.20

Melting Point: N/A Solubility In Water: Easily dispersible

Partition Coefficient (n-octanol/water): N/A

Auto Ignition Temperature: N/A **Decomposition Temperature:** N/A

Max Voc: < 50g/L

Flash Point: N/A Evaporation Rate: N/A Flammability: N/A

Boiling Point: $>100^{\circ}$ C / 212° F

Section X - STABILITY AND REACTIVITY

Reactivity: None known under normal conditions

Stability: Stable

Hazardous Reactions: None known under normal conditions **Conditions to avoid:** Keep from freezing and extreme heat

Incompatibility: Strong oxidizers

Hazardous Decomposition Products: Combustion may yield fumes, smoke, carbon monoxide and carbon

dioxide.

Section XI - TOXICOLOGICAL INFORMATION

Health Effects

Eye Contact: Minor irritation may result Skin Contact: Minor irritation may result Ingestion: Minor irritation may result Inhalation: Minor irritation may result

Toxicological Effects

Component	CAS#	Acute oral toxicity LD50	Acute dermal toxicity LD50
Petroleum Asphalt	8052-42-4	5,001 mg/kg (rat)	2,001 mg/kg (rat)
Crystalline Silica	14808-60-7	1,300 mg/kg (rat)	no data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization: Product not known to cause sensitization

Mutagenic Effects: None known Carcinogenicity: May cause cancer

Component	CAS#	<u>IARC</u>	NTP	<u>OSHA</u>
Petroleum Asphalt	8052-42-4	2B	Suspected	
Crystalline Silica	14808-60-7	Group 1	Known	

Crystalline silica in respirable form is carcinogenic to humans. The crystalline silica present is not respirable as this product is supplied. IARC has determined that there is inadequate evidence of carcinogenic effects of petroleum asphalt in humans, and limited evidence of carcinogenic effects to experimental animals.

Reproductive Toxicity: No toxicity known STOT – Single Exposure: None Known STOT – Repeated Exposure: None Known Chronic Toxicity: No Known Effect Target Organ Effects: Eyes, Skin.

Aspiration Hazard: Based on available data, the classification criteria are not met.

Numerical Measures of Toxicity

No data available

Section XII - ECOLOGICAL INFORMATION

Ecological Fate: No data available

Persistence/Degradability:No data available **Bioaccumulation Potential:**No data available

Mobility in Soil: No data available
Other Adverse Effects: No data available

Analysis for ecological effects has not been conducted.

Section XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Information: Dispose of in accordance with federal, state, and local regulations.

Section XIV - TRANSPORT INFORMATION

DOT

Proper Shipping Name: Not regulated

UN Number: N/A Hazard Class: N/A

Section XV - REGULATORY INFORMATION

International Inventories

TSCA: Complies

US Federal Regulations

SARA 313: This product contains no chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372)

SARA Hazard Category (311/312): Non Hazardous

CWA (Clean Water Act): This product contains no chemicals regulated by the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA: This product contains no substances regulated by the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

Component Name		State Right to Know		
	CAS	MA	NJ	PA
Petroleum Asphalt	8052-42-4	yes	yes	yes
Mineral Filler	1332-58-7	yes	yes	yes
Crystalline Silica	14808-60-7	yes	yes	yes
Water	7732-18-5	no	no	no

California Prop 65:

WARNING! This product contains a chemical known to the State of California to cause cancer: Asphalt (CAS-No: 8052-42-4) and Crystalline Silica (CAS-No: 14808-60-7).

International Regulations

WHMIS: Non Hazardous

Section XV - OTHER INFORMATION

Other precautions:

Keep out of reach of children.

Always read label plus precautions and follow directions carefully.

Do not breathe vapor or spray mist.

Use only with adequate ventilation.

Do not take internally.

Avoid contact with eyes and skin.

Wash thoroughly after using.

Additional Technical Data Sheets and/or SDS are available upon request.

NFPA Rating: Health 1; Fire 1: Reactivity 0

Revision Date: 04/01/15 Supersedes: 08/24/12 Prepared by: RL

Disclaimer/Statement of Liability:

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.