

# Shell Canada Limited Material Safety Data Sheet

Effective Date: 2007-11-14 Supersedes: 2004-11-26

# **1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT:	FormulaShell* ATF/ LTA
SYNONYMS:	Automatic Transmission Fluid
PRODUCT USE:	Lubricating oil

SUPPLIER	TELEPHONE NUMBERS	
Shell Canada Limited (SCL)	Shell Emergency Number	1-800-
P.O. Box 100, Station M	CANUTEC 24 HOUR EMERGENCY NUMBER	613-99
400-4th Ave. S.W.	For general information:	1-800-
Calgary, AB Canada	For MSDS information:	403-69
T2P 2H5	(From 7:30 to 4:30 Mountain Time)	

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

\*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

# 2. COMPOSITION / INFORMATION ON INGREDIENTS

THIS PRODUCT IS NOT A WHMIS CONTROLLED SUBSTANCE. See Section 8 for Occupational Exposure Guidelines.

# 3. HAZARDS IDENTIFICATION

Physical Description:	Liquid Red Colour Slight Hydrocarbon Odour
Routes of Exposure:	Exposure will most likely occur through skin contact or from inhalation of mechanically or thermally generated oil mists.
Hazards:	
	This product is not expected to be irritating and has a low level of toxicity under normal use. Inhalation of oil mist or vapours from hot oil may cause irritation of the upper
	respiratory tract.

For further information on health effects, see Section 11.

4. FIRST AID	
Eyes:	Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.
Skin:	Wipe excess from skin. Wash contaminated skin with mild soap and water for at least 15 minutes. If irritation occurs and persists, obtain medical attention. If material is injected under the skin, get medical attention promptly to prevent serious damage; do not wait for symptoms to develop.

425-106 Revision Number: 7

I-800-661-7378 513-996-6666 I-800-661-1600 403-691-3982

5. FIRE FIGHTING MEASURES		
Extinguishing Media:	Dry Chemical	
	Carbon Dioxide	
	Foam	
	Water Fog	
Firefighting Instructions:	Caution, spilled material is slippery. Material will not burn unless preheated.	
	Product will float and can be reignited on surface of water. Do not use a direct stream of water as it may spread fire. Use water to cool fire exposed containers. Water may be used to flush spills away from exposure. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.	
Hazardous Combustion Products:	Carbon monoxide, carbon dioxide and dense smoke are produced on combustion.	

# 6. ACCIDENTAL RELEASE MEASURES

Eliminate all ignition sources. Isolate hazard area and restrict access. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Spilled material is slippery. Dike and contain land spills; contain spills to water by booming. For large spills remove by mechanical means and place in containers. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Notify appropriate environmental agency(ies). After area has been cleaned up to the satisfaction of regulatory authorities, flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations.

# 7. HANDLING AND STORAGE

**Handling:** Avoid excessive heat, formation of oil mist, breathing of vapours and mist of hot oil and prolonged or repeated contact with skin. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.

**Storage:** Store in a cool, dry, well ventilated area, away from heat and ignition sources.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

The following information, while appropriate for this product, is general in nature. The selection of personal protective equipment will vary depending on the conditions of use.

#### OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Oil mist (mineral): 5 mg/m3 (STEL: 10 mg/m3)

MechanicalNot normally required. Local ventilation is recommended if oil mist is present or if<br/>exposure limit is exceeded. Make up air should always be supplied to balance air<br/>exhausted (either generally or locally).

#### PERSONAL PROTECTIVE EQUIPMENT:

**Eye Protection:** No special eye protection is routinely necessary. Wear safety glasses as appropriate.

# 9. PHYSICAL DATA

Physical State:	Liquid	Odour:	Slight Hydrocarbon Odour
Appearance:	Red Colour	Odour Threshold:	Not available
Pour Point, °C :	< -42 ℃	Boiling Point, ℃ :	> 315 ℃
Vapour Pressure (absolute):		Vapour Density (air = 1):	Not available
Density:		Flash Point, ${\bf C}$ :	Cleveland Open Cup > 180 ℃
Specific Gravity (Water = 1):		Lower Flammable Limit:	Not available
pH:	Not applicable	Upper Flammable Limit:	Not available
Viscosity:	6.5 - 7.7 cSt @ 100 ℃	Autoignition Temperature	Not available
Evaporation Rate (n-BuAc = 1):	Not available	Partition Coefficient ( log K <sub>ow</sub> ):	Not available
Water Solubility: Other Solvents:	Insoluble Hydrocarbon Solvents	Molecular Weight: Formula:	

## **10. STABILITY AND REACTIVITY**

Chemically Stable:	Yes	Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No	Sensitive to Static Discharge:	No
Incompatible Materials:	Avoid strong oxidizing agents.		
Conditions of Reactivity:	Avoid exces	sive heat, formation of vapours or mist	ts.

# **11. TOXICOLOGICAL INFORMATION**

Routes of Exposure:	Exposure will most likely occur through skin contact or from inhalation of mechanically or thermally generated oil mists.
Irritancy:	This product is not a primary skin irritant after exposure of short duration, is not a skin sensitizer and is not irritating to the eyes.
Acute Toxicity:	This product is not expected to be irritating and has a low level of toxicity under normal use.
Chronic Effects:	Prolonged or repeated contact may cause various forms of dermatitis including folliculitis and oil acne. Long term intensive exposure to oil mist may cause benign lung fibrosis.

### **12. ECOLOGICAL INFORMATION**

Environmental Effects:	The immediate effect of a release is the physical impairment of the environment from the coating of surfaces, resulting in the disruption of oxygen, water and light to flora and fauna. Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities.
Biodegradability:	Not readily biodegradable.

#### **13. DISPOSAL CONSIDERATIONS**

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site.

## **14. TRANSPORTATION INFORMATION**

#### Canadian Road and Rail Shipping Classification:

This product is not regulated under the Canadian Transportation of Dangerous Goods Regulations for transport by road and rail.

## **15. REGULATORY INFORMATION**

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

	THIS PRODUCT IS NOT A WHMIS CONTROLLED SUBSTANCE.
DSL/NDSL Status:	This product, or all components, are listed on the Domestic Substances List,
	as required under the Canadian Environmental Protection Act. This product
	and/or all components are listed on the U.S. EPA TSCA Inventory.
Other Regulatory Status:	No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial
	criteria are likely and should be requested when notifying provincial authorities.

#### **16. ADDITIONAL INFORMATION**

**Revisions:** 

This MSDS has been reviewed and updated. Changes have been made to: Section 1 Section 3 Section 4 Section 5 Section 6 Section 7 Section 8 Section 10 Section 11 Section 12 Section 13

Section 15