

1. Identification

Product identifier **POWER-STRIP**

Other means of identification

SDS number 573N-33A

Product code HIL00150

Recommended use Stripper

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.
 St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300
 (Only in the event of chemical emergency involving a spill, leak, fire, exposure, or accident involving chemicals.)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1
 Serious eye damage/eye irritation Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. Causes serious eye damage.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not take internally. Keep container closed when not in use

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Silicic acid, Sodium Salt		6834-92-0	5 - < 10
Ethanol, 2-amino-		141-43-5	3 - < 5
Benzyl Alcohol		100-51-6	1 - < 3
Other components below reportable levels			80 - < 90

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethanol, 2-amino- (CAS 141-43-5)	PEL	6 mg/m ³ 3 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethanol, 2-amino- (CAS 141-43-5)	STEL	6 ppm
	TWA	3 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethanol, 2-amino- (CAS 141-43-5)	STEL	15 mg/m ³
	TWA	6 ppm 8 mg/m ³ 3 ppm

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Benzyl Alcohol (CAS 100-51-6)	TWA	44.2 mg/m ³ 10 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical safety goggles when working with concentrate.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards None known.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear, reddish brown liquid

Physical state Liquid.

Form Liquid.

Color Not available.

Odor non-objectionable odor

Odor threshold	Not available
pH	13 - 13.7
Melting point/freezing point	Not available / Not applicable
Initial boiling point and boiling range	205 °F (96.11 °C) Corr.
Flash point	> 200.0 °F (> 93.3 °C) Tag Closed Cup
Evaporation rate	< 1 Slower than 1 Ethyl ether = 1
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	17.2 mm Hg
Vapor density	0.76 Air=1
Relative density	1.059 at 77°F
Solubility(ies)	
Solubility (water)	Appreciable
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Density	8.82 lb/gal
Percent volatile	90 - 92 %
VOC (Weight %)	6 % EPA VOC 4 % CARB VOC

10. Stability and reactivity

Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Do not mix with other chemicals. Contact with incompatible materials.
Incompatible materials	Acids. Oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns.
	Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
POWER-STRIP		
Acute		
<i>Dermal</i>		
LD50	Rabbit	93560.3125 mg/kg estimated 12809.4727 ml/kg estimated
<i>Inhalation</i>		
LC100	Rat	10526.3154 mg/l, 8 Hours estimated
LC50	Rat	52631.5781 mg/l, 8 Hours estimated
<i>Oral</i>		
LD50	Mouse	28156.8652 mg/kg estimated
	Rat	17380.1641 mg/kg estimated
Components	Species	Test Results

Benzyl Alcohol (CAS 100-51-6)

Acute

Dermal

LD50

Rabbit

2000 mg/kg

Inhalation

LC100

Rat

200 - 300 mg/l, 8 Hours

LC50

Rat

1000 mg/l, 8 Hours

Oral

LD50

Mouse

1580 mg/kg

Rabbit

1940 mg/kg

Rat

1230 - 3100 mg/kg

Ethanol, 2-amino- (CAS 141-43-5)

Acute

Dermal

LD50

Rabbit

1025 mg/kg

Oral

LD50

Guinea pig

620 mg/kg

Mouse

700 mg/kg

Rat

10.2 g/kg

Silicic acid, Sodium Salt (CAS 6834-92-0)

Acute

Oral

LD50

Mouse

2400 mg/kg

Rat

1280 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	May be harmful if absorbed through skin. Prolonged inhalation may be harmful. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species		Test Results
POWER-STRIP			
Aquatic			
Crustacea	EC50	Daphnia	66519.9922 mg/l, 48 hours estimated
Fish	LC50	Fish	8266.3018 mg/l, 96 hours estimated
Components	Species		Test Results
Ethanol, 2-amino- (CAS 141-43-5)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	114 - 196 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethanol, 2-amino- -1.31

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not contaminate ponds, waterways or ditches with chemical or used container. Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

14. Transport information

DOT

UN number	UN1760
UN proper shipping name	Corrosive liquid, n.o.s. (Sodium metasilicate)
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	Corrosive
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ERG number 154

IATA

UN number UN1760

UN proper shipping name Corrosive liquid, n.o.s. (Sodium Metasilicate)

Transport hazard class(es)

Class 8

Subsidiary risk -

Label(s) Corrosive

Packing group II

Environmental hazards No.

ERG Code 154

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed.

Cargo aircraft only Allowed.

IMDG

UN number UN1760

UN proper shipping name CORROSIVE LIQUID, N.O.S. (Sodium Metasilicate)

Transport hazard class(es)

Class 8

Subsidiary risk -

Label(s) Corrosive

Packing group II

Environmental hazards

Marine pollutant No.

EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - No
	Fire Hazard - No
	Pressure Hazard - No
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical	No
--	----

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Safe Drinking Water Act (SDWA)	Not regulated.
---------------------------------------	----------------

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. Massachusetts RTK - Substance List

Benzyl Alcohol (CAS 100-51-6)
Ethanol, 2-amino- (CAS 141-43-5)

US. New Jersey Worker and Community Right-to-Know Act

Ethanol, 2-amino- (CAS 141-43-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzyl Alcohol (CAS 100-51-6)
Ethanol, 2-amino- (CAS 141-43-5)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-04-2015
Version #	01
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 0

Disclaimer

No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.