

MSDS: B9295

ITEM: 2C928 - Blue Layout Fluid

ORDER: 0141405838

LP NUMBER: U860264712

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - B9295

Associated Grainger Items
2C928, 2C936, 2C945, 2C956, 2C967

TIW DYKEM(R*)

MATERIAL SAFETY DATA SHEET

HMIS (R*):
HEALTH 2
FLAMMABILITY 3
REACTIVITY 1
PERSONAL PROTECTION B

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

IDENTITY: STEEL BLUE LAYOUT FLUID, TRANSPARENT BLUE STAINING COLOR
ITEM NO.: 80200, 80300, 80400, 80600, 80700, 80800, 80900, 81417, 81717, 81817
FORMULA: 8706
ANOTHER EXCLUSIVE PRODUCT OF: TIW DYKEM
ADDRESS (NUMBER, STREET, CITY, STATE, AND ZIP CODE):
805 EAST OLD 56 HIGHWAY
OLATHE, KS 66061-4914
EMERGENCY TELEPHONE NUMBER:
1-800-535-5053 (DOMESTIC)
1-352-323-3500 (INTERNATIONAL)
TELEPHONE NUMBER FOR INFORMATION: 1-800-443-9536 OR 1-913-397-9889
PRODUCT CLASS: LAYOUT FLUIDS, STAINING COLORS
SIGNATURE OF PREPARER (OPTIONAL): REGULATORY DEPT.
DATE PREPARED: 4/09/10

NOTE:
BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY, COMMON NAME(S))	CAS NO.	OSHA PEL	ACGIH TLV	OTHER LIMITS % (OPT.) RECOMMENDED
ETHANOL	64-17-5	TWA: 1000 PPM	NO DATA 1000 PPM	30 - 50
BUTYL ACETATE	123-86-4	TWA: 150 PPM	TWA: 150 PPM	NO DATA 20 - 30
BUTANOL	71-36-3	TWA: 50 PPM	NO DATA 50 PPM	10 - 20
NITROCELLULOSE	9004-70-0	NO DATA	NO DATA	NO DATA 1 - 5
n-PROPYL ACETATE	109-60-4	TWA: 200 PPM	TWA: 200 PPM	NO DATA 1 - 5
ISOPROPANOL	67-63-0	TWA: 400 PPM	TWA: 400 PPM	NO DATA 1 - 5
MALACHITE GREEN	569-64-2	NO DATA	NO DATA	NO DATA <1
METHYL VIOLET	8004-87-3	NO DATA	NO DATA	NO DATA <1

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: BLUE THIN VISCOSITY LIQUID WITH SWEET SOLVENT ODOR.
WARNING:
FLAMMABLE LIQUID AND VAPOR. KEEP AWAY FROM HEAT SPARKS AND FLAMES. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. IF SWALLOWED DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.
POTENTIAL HEALTH EFFECTS:
EYES: LIQUID IS MODERATELY IRRITATING TO THE EYES.
SKIN: LIQUID IS MILDLY IRRITATING TO THE SKIN.
INGESTION: INGESTION OF LIQUID MAY CAUSE VOMITING.
INHALATION:
HIGH CONCENTRATION OF VAPORS MAY PRODUCE IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, DIZZINESS, AND NAUSEA.
CHRONIC HEALTH EFFECTS:
PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN SENSITIZATION OR DERMATITIS. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH IRREVERSIBLE BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING OR INHALING THIS PRODUCT MAY BE HARMFUL OR FATAL.

SECTION 4 FIRST AID MEASURES

EYES:
IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET

MEDICAL ATTENTION IMMEDIATELY.

INHALATION:
REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN:
FLUSH SKIN WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES.

INGESTION:
IF LARGE QUANTITIES OF THIS MATERIAL ARE SWALLOWED, GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SECTION 5 FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED): 53 F
FLAMMABLE LIMITS:
LEL: 1.40
UEL: 19.0
EXTINGUISHING MEDIA:
USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS AND TO PROTECT PERSONNEL.
SPECIAL FIRE FIGHTING PROCEDURES:
KEEP CONTAINERS COOL AND VAPORS DOWN WITH WATER SPRAY. PREVENT SPILL FROM ENTERING DRAINS, SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES. DO NOT ENTER CONTAINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.
UNUSUAL FIRE AND EXPLOSION HAZARDS:
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND, OR BE MOVED BY VENTILATION AND BE IGNITED BY IGNITION SOURCE.

SECTION 6 ACCIDENTAL RELEASE MEASURES

SMALL SPILL:
ABSORB LIQUID WITH NON-COMBUSTIBLE FLOOR ABSORBENT AND PLACE IN NON-LEAKING CONTAINER; SEAL PROPERLY AND DISPOSE OF PROPERLY IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.
LARGE SPILL:
EVACUATE AREA OF UNPROTECTED PERSONNEL. ELIMINATE ALL IGNITION SOURCES. STOP SPILL AT SOURCE IF SAFE TO DO SO. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. PREVENT SPILL FROM ENTERING DRAINS, SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES. PUMP OR VACUUM TRANSFER SPILLED PRODUCT TO CLEAN CONTAINERS FOR RECOVERY. ABSORB UNRECOVERABLE PRODUCT. TRANSFER CONTAMINATED ABSORBENT, SOIL AND OTHER MATERIALS TO CONTAINERS FOR DISPOSAL. DISPOSE OF PROPERLY IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 7 HANDLING AND STORAGE

HANDLING:
EMPTY CONTAINERS RETAIN RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRACE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, SPARKS, FLAMES, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. MANY HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED WITH AIR. IGNITION MAY OCCUR AT TEMPERATURES BELOW THOSE PUBLISHED IN THE LITERATURE AS "AUTOIGNITION" OR IGNITION TEMPERATURES. IGNITION TEMPERATURES DECREASE WITH INCREASING VAPOR VOLUME AND VAPOR VOLUME AND VAPOR/AIR CONTACT TIME, AND ARE INFLUENCED BY PRESSURE CHANGES. IGNITION OF ORGANIC CHEMICAL VAPORS MAY OCCUR AT TYPICAL ELEVATED-TEMPERATURE PROCESS CONDITIONS, ESPECIALLY IN PROCESSES OPERATING UNDER VACUUM IF SUBJECTED TO SUDDEN INGRESS OF AIR, OR OUTSIDE PROCESS EQUIPMENT OPERATING UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPORS OR MISTS TO THE ATMOSPHERE OCCURS. ANY PROPOSED USE OF THIS PRODUCT IN ELEVATED-TEMPERATURE PROCESSES SHOULD BE THOROUGHLY EVALUATED TO ASSURE THAT SAFE OPERATING CONDITIONS ARE ESTABLISHED AND MAINTAINED.

STORAGE:
KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE. STORE IN COOL, WELL-VENTILATED PLACE AWAY FROM INCOMPATIBLE MATERIALS.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE):
NOT USUALLY NECESSARY. USE WITH ADEQUATE VENTILATION. USE NIOSH/MSHA APPROVED RESPIRATOR IF PELS OR TLVs ARE EXCEEDED.

ENGINEERING CONTROLS:
LOCAL EXHAUST: NOT USUALLY NEEDED
MECHANICAL (GENERAL): YES
SPECIAL: NONE
OTHER: NONE

PROTECTIVE GLOVES:
CHEMICAL RESISTANT GLOVES (NITRILE) IF SKIN CONTACT IS POSSIBLE (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER). REPLACE GLOVES IF THEY SHOW SIGNS OF WEAR.

EYE PROTECTION:
NOT NORMALLY REQUIRED IF USED AS INTENDED. WEAR CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATION IF SPLASHING IS POSSIBLE.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:
NOT USUALLY NECESSARY. FOR BULK MATERIAL, IF DIRECT CONTACT IS POSSIBLE, WEAR APRON, BOOTS, FACE SHIELD, ETC. AS NEEDED.

WORK/HYGIENIC PRACTICES:
FOLLOW LABEL INSTRUCTIONS. WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, SMOKING, USING RESTROOMS, ETC.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 170 DEG. F - 257 DEG. F
SPECIFIC GRAVITY (H2O = 1) @ 70 DEG. F: 0.85
VAPOR PRESSURE (MM-Hg) @ 70 DEG. F: NO DATA
MELTING POINT: NO DATA
VAPOR DENSITY (AIR = 1): GREATER THAN ONE (1)
EVAPORATION RATE (BUTYL ACETATE = 1): GREATER THAN (1)
SOLUBILITY IN WATER: NEGLIGIBLE
PH: NO DATA
APPEARANCE AND ODOR: BLUE THIN VISCOSITY LIQUID WITH SWEET SOLVENT ODOR.
VOC: THIS PRODUCT CONTAINS 790 GRAMS PER LITER OR 93.24% BY WEIGHT VOC'S.

SECTION 10 STABILITY AND REACTIVITY

CHEMICAL STABILITY:
UNSTABLE ()
STABLE (X)
CONDITIONS TO AVOID: NONE KNOWN.
INCOMPATIBILITY (MATERIALS TO AVOID):
STRONG OXIDIZING AND REDUCING AGENTS, STRONG ALKALIES AND STRONG ACIDS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS:
CARBON DIOXIDE, CARBON MONOXIDE, SMOKE, SOOT AND VARIOUS ORGANIC OXIDATION BY-PRODUCTS.
HAZARDOUS POLYMERIZATION:
MAY OCCUR ()
WILL NOT OCCUR (X)
CONDITIONS TO AVOID: NO DATA

SECTION 11 TOXICOLOGICAL INFORMATION

	ORAL LD50 (RAT)	DERMAL LD50 (RABBIT)	INHALATION LC50 (RAT)
ETHANOL	7060 MG/KG	NO DATA	20000 PPM/10H
BUTYL ACETATE	14 G/KG	NO DATA	NO DATA
BUTANOL	2500 MG/KG	SLIGHT	>8000 PPM/4H
NITROCELLULOSE	>5000 MG/KG	NO DATA	NO DATA
ISOPROPANOL	5045 MG/KG	NO DATA	NO DATA

PLEASE REFER TO SECTION 3 FOR AVAILABLE INFORMATION ON POTENTIAL HEALTH EFFECTS.

SECTION 12 ECOLOGICAL INFORMATION

NO SPECIFIC ECOLOGICAL DATA ARE AVAILABLE FOR THIS PRODUCT. PLEASE REFER TO SECTION 6 FOR INFORMATION REGARDING ACCIDENTAL RELEASES AND SECTION 15 FOR REGULATORY REPORTING INFORMATION.

SECTION 13 DISPOSAL CONSIDERATIONS

DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION 14 TRANSPORT INFORMATION

(NOT MEANT TO BE ALL INCLUSIVE)

DOMESTIC HIGHWAY (CONTAINERS <1 QUART ARE ORM-D):
PROPER SHIPPING NAME: PAINT
HAZARD CLASS/SUBSIDIARY HAZARD: 3
UN/NA NO.: UN1263
PACKING GROUP: II
LABEL REQUIRED: FLAMMABLE LIQUID (3)
DOMESTIC AIR SHIPMENTS: VARIES
PROPER SHIPPING NAME: NO DATA
HAZARD CLASS/SUBSIDIARY HAZARD: NO DATA
UN/NA NO.: NO DATA
PACKING GROUP: NO DATA
LABEL REQUIRED: NO DATA

SECTION 15 REGULATORY INFORMATION

(NOT MEANT TO BE ALL INCLUSIVE - SELECTED REGULATIONS REPRESENTED)

U.S. FEDERAL REGULATIONS:

TSCA: COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

CARCINOGENICITY:
NTP?: NO
IARC MONOGRAPHS?: NO
OSHA REGULATED?: NO

OSHA:
HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

SECTION 313:

THIS PRODUCT CONTAINS BUTANOL (71-36-3) WHICH IS LISTED AND MAY REQUIRE REPORTING UNDER SARA TITLE III SEC. 313 IF USED OVER THE THRESHOLD REPORTING QUANTITY. THIS INFORMATION MUST BE INCLUDED IN ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:
THIS PRODUCT IS NOT KNOWN TO CONTAIN ANY MATERIAL LISTED UNDER CALIFORNIA'S PROPOSITION 65.

SECTION 16 OTHER INFORMATION

MSDS STATUS:

REVISED SECTION(S):
3/14/06 - ADDED 80700 TO PART NUMBERS.
4/09/10 - UPDATED W/CURRENT DATE

WARNING:

THE USE OF THIS PRODUCT IS BEYOND THE CONTROL OF THE MANUFACTURER AND DISTRIBUTOR; THEREFORE, NO GUARANTEE, EXPRESSED OR IMPLIED, IS MADE AS TO THE EFFECTS OF SUCH OR THE RESULTS TO BE OBTAINED IF NOT USED IN ACCORDANCE WITH DIRECTIONS OR ESTABLISHED SAFE PRACTICE. THE USER MUST ASSUME ALL RESPONSIBILITY, INCLUDING INJURY OR DAMAGE, RESULTING FROM ITS MISUSE AS SUCH, OR IN COMBINATION WITH OTHER MATERIALS. THE MANUFACTURER AND DISTRIBUTOR WARRANT ONLY THAT THIS PRODUCT MEETS THE SPECIFICATIONS FOR SUCH PRODUCT. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER OF THIS PRODUCT. THE MANUFACTURER AND DISTRIBUTOR SHALL BE IN NO WAY RESPONSIBLE FOR THE PROPER USE OF THIS PRODUCT. THE SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER AND DISTRIBUTOR FOR BREACH OF WARRANTY SHALL BE REIMBURSEMENT OF THE PURCHASE PRICE OF THE PRODUCT IN THE EVENT THAT A DEFECTIVE CONDITION OF THE PRODUCT SHALL BE FOUND TO EXIST. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.